

## Mobile

### SM 625 E

Up to 1" 4SH  
Opening 10 mm  
1100 kN crimping force



### SM 625

Up to 1" 4SH  
Opening 10 mm  
1100 kN crimping force  
Without led indicator


### SM 25 L HP

Up to 1 1/2", 1" 4SH  
Opening 15 mm  
1200 kN crimping force



### SM 25 L AP

Up to 1 1/2", 1" 4SH  
Opening 15 mm  
1200 kN crimping force



### SM 25 L AC

Up to 1 1/2", 1" 4SH  
Opening 15 mm  
1200 kN crimping force



## Workshop

### SM 32 MC

Up to 1 1/4"  
Opening 15 mm  
1450 kN crimping force



### SM 32 M

Up to 1 1/4"  
Opening 20 mm  
1450 kN crimping force



### SM 38 EC/SC

Up to 1 1/2"  
Opening 30 mm  
1650 kN crimping force  
Digital control



### SM 38 M

Up to 1 1/2"  
Opening 30 mm  
1650 kN crimping force  
Micrometer control



### YL-20

Up to 1 1/4"  
Opening 26 mm  
1700 kN crimping force



### YL-20 S

Up to 1 1/4"  
Opening 26 mm  
1700 kN crimping force



### YL-32

Up to 2"  
Opening 32 mm  
2200 kN crimping force



## Serial Production

### YL-65

Up to 2"  
Opening 65 mm  
2400 kN crimping force



### YL-65 S

Up to 2"  
Opening 65 mm  
2800 kN crimping force



### YL-80

Up to 4"  
Opening 80 mm  
3200 kN crimping force



## Side feed

### YL-SF 60

Up to 1 1/4"  
Opening  
25 mm / 48 mm  
350 kN crimping force

